

1	D== d=t	Coocification	far F	D0004	7 0400
	Product	Specification	ons for E	P9031/	7-91PC

•	Todast opesitionis for Er oco ir o ir o		
	Job Name:	Job Type:	
	Quantity:	Comments	

EP96317-91PC

Measurements

N/A

LED

N/A

N/A

No

Other

UPC Code

Material

Low-Voltage

Electronic Dimmer

Harmony LED RapidJack Pendant



Finish Polished Chrome

Number of Bulb(s)

Lamping

Light Type Bulb Type LED Max Bulb Wattage 1.5 Max Fixture Wattage 1.5 **Rated Life** N/A **Rated Lumens** ±105 Color Temp 3000K Bulb(s) Included Yes Light Up/Down N/A **Beam Spread** N/A

Certification

Photo Cell Included

Dimmable

Ballast/Driver/Transformer

Safety Rating Dry **Energy Star** No CA Title 24 No CA Title 20 No ADA No

Glass/Shade	Product Category	
Bubble	RapidJack Pendant	

Width	3.15"
Height	3.15"
Length	3.15"
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	3.75"
May Overall Height	122 75"

N/A 3.75" 123.75" Max Overall Height Hanging Weight 1.26 lb(s) **Height Adjustable** N/A Slope N/A Chain Length N/A Wire Length N/A N/A **Canopy Width** N/A **Canopy Height Canopy Length** N/A

Shipping	
Carton Weight	1.54 lb(s)
Carton Width	8.50"
Carton Height	7.50"
Carton Length	8.50"
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Equivalents

845094071402	Incandescent Watts	N/A
N/A	Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2016 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.