


Project:

Light Frames Up/Down LED Sconce Spec Sheet

SKU: 7202.98-WL Learn more at:
<https://sonnemanlight.com/light-frames-up-2fdown-led-sconce>

Description: LED illumination is directed downward from the interior top edge of the frame within a broad rectilinear column. Also available as a [Sconce](#) and [Bollard](#).

Type #:



Dimensions

Height:	14"
Width:	7"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Size:	14"
Canopy/Backplate/Base Depth:	6.5
Canopy/Backplate/Base Height:	4.5

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Input Voltage:	120VAC
Wattage:	21
Initial Lumens:	2570
Delivered Lumens:	1260
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	21

Installation

Installation:	Licensed electrician required
Installation Orientation:	Vertical

Shipping

Carton 1 L x W x H:	16" X 9" X 5"
Carton 1 Gross Weight:	5 LBS
Fixture Weight:	4

Shade

Shade 1 Material:	Aluminum
-------------------	----------

Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

General Listings

Features:	Wet Rated
Certification:	C-ETL-US
Color/Finish:	Textured White (.98)
Dark Sky Friendly:	N