

A800026-1-S INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL


All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY AND INSTALLATION

- 1. Secure the mounting bar(9) to the outlet box(1) with box screws(6).
- 2. Pull the outlet wire and ground wire out from the outlet box. Make wire connections with wire connector(2)
- --Black wire from light to Black wire (3) from power source.
- --White wire from light to White wire(4) from power source.
- --Loop the ground wire(5) to mounting bar(9) with a ground screw (10).
- 3. Attach the canopy(11) against the outlet box (1). Secure with the ball nut (12) and mounting screw(7).
- 4. Loosen the glass holder (13), and slide the crystal (14) up the cable.
- 5. Insert G9 bulb (15, not included) into socket.
- 6. Slide the crystal back down the cable and tighten the glass holder (13).

DO NOT USE BARE HANDS TO TOUCH THE G9 BULB.



- 1. OUTLET BOX
- WIRE CONNECTOR
- 3. BLACK WIRE
- WHITE WIRE
- 5. GROUND WIRE
- **BOX SCREW**
- 7. MOUNTING SCREW
- 8. HEX NUT
- 9. MOUNTING BAR
- 10. GROUND SCREW
- 11. CANOPY
- 12. BALL NUT
- 13. GLASS HOLDER
- 14. K9 CRYSTAL
- 15. G9 BULB