

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

**MIN 90°C SUPPLY CONDUCTORS**  
**CAUTION-RISK OF FIRE CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR**

**WARNING:** Be sure the electricity to the wires you are working on is shut off, either the fuse is removed or the circuit breaker is shut off.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirements.

Carefully remove the fixture from the carton, and check that all parts are included, as shown in figure. Be careful not to misplace any of the screws or parts which are needed for installing the fixture.

## Assembly and Installation Step:

1. Attach the Nipple to the Mounting Bar, and then secure with the Washer and the Nut.
2. Attach the Mounting Bar to the Outlet box (not supplied) by using 2 Outlet Box Screws.
3. Make wire connections with wire nuts:
  - a. The black wire from fixture to the black wire from power source.
  - b. The white wires from fixture to the white wire from power source.
  - c. Attach the ground wire and house ground wire to the cross bar with a green ground screw.
4. Attach the Fixture to the Mounting Bar by inserting the Nipple, and then secure with the End Cap.
5. Install lamp.
6. Turn on the power at fuse or circuit box.

