




Cap for Non-Light Use (Incl.)

Image File Name: F888-ORB.jpg



MEASUREMENTS

Blade Finish:			Reversible Blades:		
			No		
Blade Material:			Slope:		
ABS Construction			Yes		
Blade Sweep:	No. of Blades:	Blade Pitch:	Hanging Weight:		
65"	8	14	26.41		
Downrod 1:	Downrod 1 Outside	Downroad 2:	Downrod 2 Outside		
6	Dia:		Dia:		
	0.75				
Ceiling to Lowest	Ceiling to Blade	Lead Wire:	Motor Size:		
Point: (Dim A)	(Dim B)	80	DC 165x25mm		
14.75	10.5				

	Low	Low/Med.	Medium	Med/High	High
RPM:	78		86		98
Amps:	0.203		0.264		0.363
Watts:	14.5		19.5		27.6
CFM:	7107.0		7734.0		8778.0
CFM/Watts:	490.14		396.62		318.04

LAMPING

No. of Bulbs:	Light Type:				
1	SEMI SPIRAL CFL				
Max Bulb	Socket:				
Wattage:	GU24				
18					
Light Kit:	Dimmable:	Ballast:	Rated Life	Uplight:	
Yes	No		Hours:	No	
Bulb/LED	Color Temp.:	CRI:	Initial Lumens:	Delivered	
Included:			Lumens:		

GLASS

Description:	Material:	
Tinted Opal	GLASS	
Part No.:	Quantity:	
GF888-2	1	
Width:	Height:	Length:
8.5	3.0	8.5



FAN CONTROLS

Pull Chain	Works with Remote Control:	Works with Wall Control:
Control:	Yes	Yes
No		
	Included Remote Control:	Included Wall Control:
	RC400	
	Compatible Remote	Compatible Wall Control(s):
	Control(s):	WC400



SHIPPING

Carton Width:	Carton Height:	Carton Length:
11.25	11.63	32.75
Carton Weight:	Carton Cubic Feet:	Small Package Shippable:
29.83	2.48	Yes
Master Pack Width:	Master Pack Height:	Master Pack Length:
Master Pack Weight:	Master Cubic Feet:	Multi-Pack:
		Master Pack:
		1



Wet
Location



Title 17



ETL
Intertek

For additional information, please contact Customer Care: 1-800-221-7977 | Product depicted on this spec sheet is protected by United States Federal and/or State laws including US Patent, Trademark and/or Copyright and unfair competition laws. Unauthorized reproduction or use carries severe legal penalties.