START FROM HERE

- Make sure power is completely off at the fuse box.
- · Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area.
- Wear gloves at all times during this installation.
- Read instructions carefully before you start assembly.
- Keep this instruction sheet for future reference.

Technical Support: 1-855-855-8926

- Please Note:
- 120V input

- 1. Remove the fixture from its original packaging.
- 2. Remove the mounting plate (1c) from the canopy (2a) by removing the decorative nuts (2c)
- **3.** Align mounting plate screws (1d) to desired orientation, and then attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package
- **4.** To change fixture height, shorten or lengthen wire by removing screw **(2b)** from canopy **(2a)** and push or pull wire to your desired length. Secure screw **(2b)** in canopy **(2a)** to lock wire in place
- **5.** Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **6.** Align and insert mounting plate screws (1d) through holes on canopy (2a), secure with decorative nuts (2c)
- 1. Install bulb into the fixture (bulb not included) and pull up fixture socket (3b) into the fixture (3a). Attach fixture end (3c) to fixture (3a) to close



