

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Vornado Chandelier 3000K

Model & Size	Color Temp	Finish	Watt	LED Lumens	Delivered Lumens
PD-87720 20"	3000K	CH Chrome	30.5W	2825	2075
	3000K	WT White	30.5W	2825	2075

Example: **PD-87720-CH**

### DESCRIPTION

Harmony out of chaos, Vornado is a free flowing mobius strip of high-powered LED illumination. A simple, yet dynamic piece, Vornado is hand crafted to perfection. The flexible" composite diffuser maximizes brightness and eliminates LED hot spot. Vornado is suspended on four thin low profile cables without the need for an additional power cord, lending to a " simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

### FEATURES


- Free flowing mobius strip of light
- Simple yet dynamic statement piece
- Each piece is hand crafted. Expect slight variations.
- Frosted extruded diffuser creates even illumination
- Assembled with a frosted joint clip, with optional chrome clip included
- Cable suspension carrying low voltage may be field shortened
- 0-10V dimming available for PD-87720 only
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS


<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>CRI:</b>	90, 80
<b>Dimming:</b>	ELV: 100 - 5%, 0-10V: 100-5%, ELV: 100-10%, 0-10V: %
<b>Rated Life:</b>	60000 Hours
<b>Standards:</b>	ETL, cETL, Title 24 JA8-2016 Compliant, Title 24: Damp Location Listed
<b>Construction:</b>	Aluminum body with flexible composite diffuser



### FINISHES



### LINE DRAWING



**PD-87720**

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Vornado Chandelier 3000K

Model & Size	Color Temp	Finish	Watt	LED Lumens	Delivered Lumens
PD-87723 23"	3000K	CH Chrome	51.9W	5106	3110
	3000K	WT White	51.9W	5106	3110

Example: **PD-87723-CH**

### DESCRIPTION

Harmony out of chaos, Vornado is a free flowing mobius strip of high-powered LED illumination. A simple, yet dynamic piece, Vornado is hand crafted to perfection. The flexible" composite diffuser maximizes brightness and eliminates LED hot spot. Vornado is suspended on four thin low profile cables without the need for an additional power cord, lending to a " simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

### FEATURES


- Free flowing mobius strip of light
- Simple yet dynamic statement piece
- Each piece is hand crafted. Expect slight variations.
- Frosted extruded diffuser creates even illumination
- Assembled with a frosted joint clip, with optional chrome clip included
- Cable suspension carrying low voltage may be field shortened
- 0-10V dimming available for PD-87720 only
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS


Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90, 80
Dimming:	ELV: 100 - 5%, 0-10V: 100-5%, ELV: 100-10%, 0-10V: %
Rated Life:	60000 Hours
Standards:	ETL, cETL, Title 24 JA8-2016 Compliant, Title 24: Damp Location Listed
Construction:	Aluminum body with flexible composite diffuser



### FINISHES



### LINE DRAWING



**PD-87723**

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Vornado Chandelier 3000K

Model & Size	Color Temp	Finish	Watt	LED Lumens	Delivered Lumens
PD-87735 35"	3000K	CH Chrome	52.1W	5278	3550
	3000K	WT White	52.1W	5278	3550

Example: **PD-87735-CH**

### DESCRIPTION

Harmony out of chaos, Vornado is a free flowing mobius strip of high-powered LED illumination. A simple, yet dynamic piece, Vornado is hand crafted to perfection. The flexible" composite diffuser maximizes brightness and eliminates LED hot spot. Vornado is suspended on four thin low profile cables without the need for an additional power cord, lending to a " simple and minimalistic design. Adjustable to different lengths through a push-pin locking mechanism at the canopy.

### FEATURES


- Free flowing mobius strip of light
- Simple yet dynamic statement piece
- Each piece is hand crafted. Expect slight variations.
- Frosted extruded diffuser creates even illumination
- Assembled with a frosted joint clip, with optional chrome clip included
- Cable suspension carrying low voltage may be field shortened
- 0-10V dimming available for PD-87720 only
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS

<b>Color Temp:</b>	3000K
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>CRI:</b>	90, 80
<b>Dimming:</b>	ELV: 100 - 5%, 0-10V: 100-5%, ELV: 100-10%, 0-10V: %
<b>Rated Life:</b>	60000 Hours
<b>Standards:</b>	ETL, cETL, Title 24 JA8-2016 Compliant, Title 24: Damp Location Listed
<b>Construction:</b>	Aluminum body with flexible composite diffuser




### FINISHES



Chrome White

LINE DRAWING



**PD-87735**